

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com





Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

### General ordering data

Version	Field attachable connector, M12, pin, straight
Order No.	<u>9456940000</u>
Туре	SAIS-5/7
GTIN (EAN)	4008190304935
Qty.	1 pc(s).

# **Technical data**



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Net weight	23 g		
Technical data customisable	e plug-in connectors		
Cable diameter, max.	6 mm	Cable diameter, min.	4 mm
Coding	A-coded	Conductor cross-section, max.	0.75 mm <sup>2</sup>
Conductor cross-section, min.	0.14 mm <sup>2</sup>	Contact surface	CuSnZn
Contact surface	CuSnZn (5-pole) / gold plated (8-pole)	Housing main material	PA
Insulation strength	10 <sup>8</sup> Ω	Number of poles	5
Plugging cycles	≥ 50	Pollution severity	3
Protection degree	 IP67	Rated current	4 A
Rated voltage	60 V	Shield connection	No
Temperature range of housing	-40 +85 ° C	Threaded ring material	Diecast zinc
Type of connection	Screw connection		Bioduct Zinte
General Info	-		
Number of poles	5	Connection 1	M12
Connection 2	Screw	Housing main material	PA
Connection thread	M12	Contact surface	CuSnZn
Protection degree	IP67	Plugging cycles	≥ 50
Standards			
Connector standard	IEC 61076-2-101		
Classifications			
ETIM 6 O	EC002635	ETIM 7.0	FC00262F
ETIM 6.0 ETIM 8.0	EC002635 EC002635	ETIM 7.0 ETIM 9.0	EC002635 EC002635
ECLASS 9.0	27-44-01-02	ECLASS 9.1	27-44-01-03
ECLASS 9.0 ECLASS 10.0	27-44-01-02	ECLASS 9.1 ECLASS 11.0	27-44-01-03
ECLASS 10.0 ECLASS 12.0	27-44-01-16	ECLASS 11.0 ECLASS 13.0	27-44-01-02
ECLASS 12.0 ECLASS 14.0	27-44-01-16		27 44-01-02
Environmental Product Complia			
p			
RoHS Compliance Status	Compliant with exemption		
RoHS Exemption (if applicable/known)	6c		
REACH SVHC	Lead 7439-92-1 Imidazolidine	-2-thione 96-45-7	
SCIP	bcee35cf-c0f5-43d2-8daf-65a	ab0d08641a	
Approvals			
Approvals			

ROHS	Conform	
UL File Number Search	UL Website	
Certificate No. (cURus)	E307231	

### Creation date November 26, 2024 1:00:28 PM CET



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Downloads	
Engineering Data	CAD data – STEP
User Documentation	<u>Manual</u>
Catalogues	Catalogues in PDF-format
Brochures	<u>FL FIELDWIRING EN</u> FL FIELDWIRING EN



Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26

D-32758 Detmold Germany

www.weidmueller.com

# Drawings

Pole scheme

