

## Main

|                               |                                 |
|-------------------------------|---------------------------------|
| Range of product              | OsiSense XC                     |
| Series name                   | Standard format                 |
| Product or component type     | Limit switch                    |
| Device short name             | XCKP                            |
| Sensor design                 | Compact form B CENELEC EN 50047 |
| Body type                     | Fixed                           |
| Head type                     | Plunger head                    |
| Material                      | Plastic                         |
| Body material                 | Plastic                         |
| Head material                 | Zamak                           |
| Fixing mode                   | By the body                     |
| Movement of operating head    | Linear                          |
| Type of operator              | Spring return plunger metal     |
| Type of approach              | Vertical approach, 1 direction  |
| Number of poles               | 2                               |
| Contacts type and composition | 1 NC + 1 NO                     |
| Contact operation             | Snap action                     |

## Complementary

|  |   |
|--|---|
| Switch actuation                             | On end  |
| Electrical connection                        | Male connector M12, 4 pins  |
| Contacts insulation form                     | Zb  |
| Positive opening                             | With  |
| Positive opening minimum force               | 45 N  |
| Minimum force for tripping                   | 15 N  |
| Minimum actuation speed                      | 0.01 m/min  |
| Maximum actuation speed                      | 0.5 m/s   |
| Repeat accuracy                              | 0.1 mm on the tripping points with 1 million operating cycles   |
| [Ie] rated operational current               | 3 A 240 V, AC-15 EN/IEC 60947-5-1 appendix A<br>0.27 A 250 V, DC-13 EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 3 A   |
| [Ui] rated insulation voltage                | 300 VUL 508<br>300 VCSA C22.2 No 14<br>250 V (pollution degree 3) conforming to IEC 60947-1   |
| Maximum resistance across terminals          | 25 MOhm IEC 60255-7 category 3  |
| [Uimp] rated impulse withstand voltage       | 2.5 KV IEC 60664<br>2.5 kV IEC 60947-1  |
| Short-circuit protection                     | 4 A cartridge fuse gG   |
| Electrical durability                        | 5000000 Cycles, DC-13, 120 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13, 24 V, 10 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 48 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C |
| Mechanical durability                        | 15000000 cycles   |
| Maximum Width                                | 1.22 in (31 mm)   |
| Height                                       | 2.56 in (65 mm)   |
| Depth  | 1.18 in (30 mm)   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |                        |
|-------------------------------|------------------------|
| Net Weight                    | 0.22 lb(US) (0.1 kg)   |
| Terminals description ISO n°1 | (13-14)NO<br>(21-22)NC |

## Environment

|                                       |   |
|---------------------------------------|---|
| Shock resistance                      | 50 gn 11 ms IEC 60068-2-27  |
| Vibration resistance                  | 25 gn 10...500 Hz)IEC 60068-2-6   |
| IP degree of protection               | IP66 conforming to IEC 60529<br>IP67 IEC 60529  |
| IK degree of protection               | IK04 EN 50102   |
| Electrical shock protection class     | Class II IEC 61140<br>Class II NF C 20-030  |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)  |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)  |
| Protective treatment                  | TC  |
| Product certifications                | CSA<br>UL<br>CCC  |
| Standards                             | UL 508<br>EN 60947-5-1<br>CSA C22.2 No 14<br>EN 60204-1<br>IEC 60204-1<br>IEC 60947-5-1 |

## Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22418 - LIMIT SWITCH,IEC,XCKP&XCKT |
| Discount Schedule     | T                                  |
| GTIN                  | 00785901990529                     |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 0.17 lb(US) (0.08 kg)              |
| Returnability         | No                                 |
| Country of origin     | ID                                 |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Height | 0.980 dm |
| Package 1 width  | 0.390 dm |
| Package 1 Length | 0.320 dm |


## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



- (1) 2 elongated holes  $\varnothing 4.3 \times 6.3$  mm on 22 mm centres, 2 holes  $\varnothing 4.3$  on 20 mm centres.
- (2) 2 x  $\varnothing 3$  holes for support studs, depth 4 mm.

---

## Mounting with Cable Entry

---

### Position of Cable Gland



- (1) Recommended
- (2) To be avoided

---

## Setting-up

---

### Plunger or Multi-directional Heads




---

## Wiring Diagram

---

2-pole NC + NO Snap Action




---

## Connections

---


M12 Connector




1-2 : NC  
3-4 : NO

Characteristics of Actuation

Switch Actuation on End



Functionnal Diagram



- (P) Positive opening point
- (1) NC contact with positive opening operation
- (2) Closed
- (3) Open
- (4) Tripping
- (5) Resetting