VW3L40210

insert - 2 female M8 for 2 I/O signals + 1 male M8 for safe torque off safety



Main	
Range of Product	Lexium integrated drive
Product or Component Type	Insert for communication interface
Accessory / separate part type	Connection accessories
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives

Complementary

Electrical connection	1 male connector M8 4 pins for connection of signals for safe torque off 2 female connectors M8 3 pins for connection of 2 I/O signals
Kit composition	1 insert with connectors 1 sealing insert
Input/output type	2 I/O signals + 1 STO signal
Net Weight	0.08 lb(US) (0.036 kg)

Ordering and shipping details

Category	18289-LEXIUM INTEGRATED DRIVES ACC
Discount Schedule	PC56
GTIN	3389118367821
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4.0 cm)
Package 1 Width	2.05 in (5.2 cm)
Package 1 Length	3.54 in (9.0 cm)
Package 1 Weight	1.27 oz (36.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	2.74 lb(US) (1.242 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫ _{Yes}
PVC free	Yes

Contractual warranty

Contractad Warranty	
Warranty	18 months