

ORDERING INFORMATION


Order code: 65499
 Description: F54T5/65K/8/HO/PS/G5/STD
 UPC: 69549654990
 Case quantity: 25




PERFORMANCE DATA

Shape: T5
 Base: G5 (Min Bipin)
 Starting method: Program Start (PS)
 Wattage (W): 54
 Colour temperature (K): 6 500
 CRI: 85
 Rated life on PS/PRS¹ ballast:
 Based on a 3 hour start 24 000
 Based on a 12 hour start 30 000
 Initial lumens (lm): 4 700
 Mean lumens (lm): 4 465
 Nominal efficiency (lm/W): 87
 TCLP compliant: Yes
 Phosphor composition: Triphosphor
 Nominal lamp operating frequency (Hz): 60
² Minimum starting temperature (°C): -10

DIMENSIONS



SPECTRAL DISTRIBUTION



¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.

² The minimum starting temperature is a function of the ballast. The minimum starting temperature is based on a STANDARD brand T5 High Output ballast.



OUTDOOR



INDOOR



WARRANTY



COMPLIANT



RECYCLABLE



ENERGY SAVING



ONE SYSTEM WARRANTY



Means this bulb meets federal minimum efficiency standards.

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

February 21, 2017

STANDARD