

YGHA26NTN Compression Grounding Lug, 2/0 AWG Cu, 1-Hole, 1/2" Stud, Tin Plated

By Burndy Catalog # YGHA26NTN

 $HYLUG^{TM}$ Copper Compression Terminal for Grounding; Heavy Duty; 1-Hole.

Features

- Irreversible compression ground terminal specifically designed for grounding applications
- Each connector has an inspection probe hole to ensure proper cable insertion
- UL467 Listed
- Acceptable for Direct Burial in earth or concrete
- UL486A Listed
- Prefilled with PENETROX[™] compound and strip sealed

General

Catalog Number YGHA26NTN
Connector Type Terminal
Die Index 15
Material Copper
Physical Attribute - Number of 1

Crimps Required

Plated

Plating Type Tin - Electro Plated

 Trade Name
 HYLUG™

 Type
 Terminals

 UPC
 781810346631

 UPC 12 Digit
 7818103466311

Dimensions

inch

Dimension - B Length fraction	39/47 in
Dimension - B Length inch	0.83 in
Dimension - D inch	1.27 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - L Length Overall	67 mm
mm	
Dimension - Length Overall	2.63 in
inch	
Dimension - N inch	0.63 in

0.71 in



Dimension - Pad Width inch

Dimension - Z (inch)

Physical Attribute - Tongue

O.97 in

O.64 in

Straight

Angle

Conductor Related

Conductor - Copper Str Size 2/0 AWG Conductor - Copper Str Size 2/0 AWG

Range

Conductor Type • CU C Str-Size

CU C Solid-Size

Certifications And Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized No Certification - cULus No

Standards - Industry Standards UL467;UL468A-468B;IEEE 837

Met

Standards - RoHS Compliance CM

Status

UL Listed No

Logistics

Carton Quantity 25
Minimum Pack Quantity 1
Pallet Quantity 11600

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - SD..211241-01

Specifications - YGHA26NTN



Dimension - Outside Diameter