



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Multi-directional head
Product compatibility	XCKJ
Associated body	ZCKJD35H29 ZCKJ1H29 ZCKJ8H7 ZCKJ21 ZCKJ6 ZCKJ9 ZCKJD39 ZCKJ9H7 ZCKJ2H7 ZCKJ11H7 ZCKJ6H7 ZCKJ5 ZCKJ21H29 ZCKJ5H7 ZCKJ8H29 ZCKJD31 ZCKJD37H29 ZCKJ7H7 ZCKJ2H29 ZCKJ11 ZCKJD37H7 ZCKJD31H7 ZCKJ1 ZCKJ7H29 ZCKJ6H29 ZCKJ21H7 ZCKJ7 ZCKJ11H29 ZCKJD39H29 ZCKJD31H29 ZCKJ8

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJD37
ZCKJD35H7
ZCKJ9H29
ZCKJD35
ZCKJ1H7
ZCKJ2
ZCKJD39H7
ZCKJ5H29

Movement of operating head	Multi-directional
Type of operator	Spring rod spring return
Type of approach	Multi-directional approach

Complementary

Switch actuation	By any moving part
Positive opening	Without
Net weight	0.28 lb(US) (0.125 kg)
Head material	Metal

Environment

Ambient air temperature for operation	-40...158 °F (-40...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Low temperature

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.73 oz (134 g)
Package 1 Height	1.54 in (3.9 cm)
Package 1 width	6.57 in (16.7 cm)
Package 1 Length	1.54 in (3.9 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Weight	7.93 lb(US) (3.595 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------