

# 9007MS10S0300

## LIMIT SWITCH 240VAC 10AMP MS +OPTIONS



### Main

Actuation	Vertical
Actuator	Booted Push Rod
Actuator Action	Momentary
Ampere Rating	10A
Application	Machine tools, earth moving equipment or general transportation
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211-03 - CE Marked
Body Material	Cast Zinc (fully potted)
Cable Length	9 Feet
Connection Type	#18 AWG SJTO Cable - Yellow
Contact Configuration	1 N.O./1 N.C.
Contact Form	Form C - SPDT
Contact Material	Silver Alloy
Contact Operation	Snap Action
Enclosure Rating	NEMA 1/2/4/6/6P/12/13; IP67
Head Type	Top Plunger
Height	2.48 Inches (62.99mm)
Maximum Voltage Rating	240VAC/28VDC
Mounting Type	Shoulder
Operating Temperature Range	-40 to +221 Degrees F
Operating Torque/Force	80 Ounces
Shock Resistance	35G
Type	MS
Type of Duty	Heavy Duty
Vibration Resistance	10G (75 to 1200Hz)
Width	1.56 Inch (40mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.