
## Product data sheet Characteristics

## NSYMR86

# Monobloc perforated plates H800xW600mm with universal perforations 11x26mm





#### Overview

Lead time Usually Ships within 4 Weeks

#### Main

| - IVICAITI                         |   |  |
|------------------------------------|---|--|
| Range                              | Spacial   |  |
| Accessory / separate part category | Mounting accessory  |  |
| Product or Component Type          | Mounting plate  |  |
| Device Application                 | Multi-purpose   |  |
| Enclosure nominal dimensions       | - H: 31.50 in (800 mm) W: 23.62 in (600 mm)<br>- H: 31.50 in (800 mm) W: 47.24 in (1200 mm) |  |
| Mounting Location                  | Step slide<br>Direct fixing on backstuds  |  |
| Mounting plate description         | Telequick perforated  |  |
| Range compatibility                | Spacial Spacial S3D<br>Spacial Spacial CRN<br>Spacial Spacial S3X<br>Thalassa Thalassa PLM  |  |
| Quantity per Set                   | Set of 1  |  |
| Material                           | steel   |  |
| Surface Finish                     | Zinc coated   |  |
|                                    |   |  |

#### Complementary

| Fixing mode           | Screwed on backstuds M8           |
|-----------------------|-----------------------------------|
| i ixiiig iiiode       |                                   |
|                       | By fixing element                 |
| Height                | 29.53 in (750 mm)                 |
| Width                 | 21.69 in (551 mm)                 |
| Depth                 | 0.59 in (15 mm)                   |
| Thickness             | 0.08 in (2 mm)                    |
| Net Weight            | 6.97 lb(US) (3.16 kg)             |
| Number of slots       | 867                               |
| Variant particularity | With enclosures H800 x W1200      |
|                       | Installation in rear of enclosure |
| Cut-out dimensions    | 11 x 26 mm                        |

#### Ordering and shipping details

| Ordering and shipping details |                                     |
|-------------------------------|-------------------------------------|
| Category                      | 80036-ENCLOSURE SYSTEMS ACCESSORIES |
| Discount Schedule             | ES1                                 |
| GTIN                          | 3606480183768                       |
| Returnability                 | Yes                                 |
| Country of origin             | FR                                  |

## Packing Units

| Unit Type of Package 1       | PCE                      |
|------------------------------|--------------------------|
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 0.79 in (2.0 cm)         |
| Package 1 Width              | 21.85 in (55.5 cm)       |
| Package 1 Length             | 29.72 in (75.5 cm)       |
| Package 1 Weight             | 7.01 lb(US) (3.18 kg)    |
| Unit Type of Package 2       | PAM                      |
| Number of Units in Package 2 | 126                      |
| Package 2 Height             | 35.43 in (90.0 cm)       |
| Package 2 Width              | 39.37 in (100.0 cm)      |
| Package 2 Length             | 47.24 in (120.0 cm)      |
| Package 2 Weight             | 945.78 lb(US) (429.0 kg) |
|                              |                          |

## Offer Sustainability

| Sustainable offer status   | Green Premium product  |
|----------------------------|--|
| REACh Regulation           | ☑ REACh Declaration  |
| REACh free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | China RoHS Declaration   |
| RoHS exemption information | ₫Yes   |
| Environmental Disclosure   | Product Environmental Profile  |
| Circularity Profile        | No need of specific recycling operations   |

### Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|          |           |