



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD37H29 ZCKJ21 ZCKJD39H29 ZCKJ1 ZCKJ4 ZCKJD31 ZCKJ8H7 ZCKJ4H7 ZCKJD31H7 ZCKJ11H29 ZCKJD35 ZCKJ2 ZCKJ41H29 ZCKJ9H29 ZCKJ41 ZCKJ11H7 ZCKJ6H29 ZCKJD39H7 ZCKJD37 ZCKJ9 ZCKJ21H29 ZCKJ4H29 ZCKJ5 ZCKJ8H29 ZCKJD31H29 ZCKJ11 ZCKJD37H7 ZCKJ41H7 ZCKJD35H29

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJ5H7
 ZCKJ21H7
 ZCKJ5H29
 ZCKJ1H29
 ZCKJ7H7
 ZCKJ6H7
 ZCKJD35H7
 ZCKJ2H7
 ZCKJ9H7
 ZCKJ7
 ZCKJ8
 ZCKJ1H7
 ZCKJD39
 ZCKJ7H29
 ZCKJ6
 ZCKJ2H29

Movement of operating head	Linear
Type of operator	End plunger spring return metal
Type of approach	Vertical approach, 1 direction

Complementary

Switch actuation	On end
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	50...248 °F (10...120 °C)
Ambient air temperature for storage	50...248 °F (10...120 °C)
Environmental characteristic	High temperature

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.04 oz (142.9 g)
Package 1 Height	1.61 in (4.1 cm)
Package 1 width	1.77 in (4.5 cm)
Package 1 Length	3.35 in (8.5 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------