

Main

| | |
|-----------------------------|--|
| Ampere Rating | 200mA |
| Ampere Rating | 200mA |
| Approvals | UL Listed - CSA Certified - CE Marked |
| Approvals | UL Listed - CSA Certified - CE Marked |
| Body Type | Tubular |
| Body Type | Tubular |
| Connection Type | M12 Connector |
| Connection Type | M12 Connector |
| Enclosure Material | Nickel Plated Brass |
| Enclosure Material | Nickel Plated Brass |
| Enclosure Rating | NEMA 3/4X/6P/12/13 |
| Enclosure Rating | NEMA 3/4X/6P/12/13 |
| Enclosure Type | Water tight, Dust tight, Oil tight, Corrosion Resistant and Submersible (Indoor/Outdoor) |
| Enclosure Type | Water tight, Dust tight, Oil tight, Corrosion Resistant and Submersible (Indoor/Outdoor) |
| LED Indicator | Output: Yellow |
| LED Indicator | Output: Yellow |
| Marketing Trade Name | Osiprox |
| Marketing Trade Name | Osiprox |
| Maximum Operating Frequency | 5000Hz |
| Maximum Operating Frequency | 5000Hz |
| Maximum Voltage Rating | 58VDC |
| Maximum Voltage Rating | 58VDC |
| Nominal Sensing Distance | 4mm |
| Nominal Sensing Distance | 4mm |
| Operating Temperature Range | -13 to 158 Degrees F (-25 to 70 Degrees C) |
| Operating Temperature Range | -13 to 158 Degrees F (-25 to 70 Degrees C) |
| Output | DC 3-Wire (PNP) - 1 N.O. |
| Output | DC 3-Wire (PNP) - 1 N.O. |
| Sensor Diameter | 12mm |
| Sensor Diameter | 12mm |
| Supply Voltage | 12/48VDC |
| Supply Voltage | 12/48VDC |
| Type | XS6 |
| Type | XS6 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.