



Main

Commercial Status	Commercialised
Range of product	Homeline
Product or component type	Load Centre
Line Rated Current	100 A
System Voltage	120/240 V AC
Mounting mode	Wall mount
Short-circuit current	22 kA

Complementary

Electrical connection	Lugs
AWG gauge	AWG 6...AWG 2/0 (aluminium/copper)
Load Centre type	Main breaker
Number of spaces	30
Number of circuits	60
Number of tandem circuit breakers	30
Phase	1 phase
Cover type	Combination flush/surface cover
Device composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Cover colour	White
Box number	10

Environment

Product certifications	CSA
NEMA degree of protection	NEMA 1 (indoor)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1411 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.