

CHANGE-OUT SERIES A STOOW MALE PLUGS WITH **NYLON** COUPLING NUT

POLES	FACE VIEW MALE	COLOR CODE	RATING	AWG	CABLE LENGTH	PART NUMBER
2		1. Black 2. White	600V, 18A	14	6' 12' 18'	X8651-79P X8651-81P X8651-83P
3		1. Black 2. White 3. Green	600V, 18A	14	6' 12' 18'	X8652-93P X8652-95P X8652-97P
4		1. Black 2. Green 3. Red 4. White	600V, 15A	14	6' 12' 18'	X8653-93P X8653-95P X8653-97P

CHANGE-OUT SERIES A STOOW FEMALE PLUGS WITH **ZINC DIECAST** COUPLING NUT

POLES	FACE VIEW FEMALE	COLOR CODE	RATING	AWG	CABLE LENGTH	PART NUMBER
2		1. Black 2. White	600V, 25A	12	6' 12' 18'	X8651-528P X8651-529P X8651-644P
3		1. Black 2. White 3. Green	600V, 25A	12	6' 12' 18'	X8652-528P X8652-529P X8652-644P
4		1. Black 2. Green 3. Red 4. White	600V, 20A	12	6' 12' 18'	X8653-528P X8653-529P X8653-644P

CHANGE-OUT SERIES A STOOW MALE PLUGS WITH **ZINC DIECAST** COUPLING NUT

POLES	FACE VIEW MALE	COLOR CODE	RATING	AWG	CABLE LENGTH	PART NUMBER
2		1. Black 2. White	600V, 25A	12	6' 12' 18'	X8651-516P X8651-517P X8651-640P
3		1. Black 2. White 3. Green	600V, 25A	12	6' 12' 18'	X8652-516P X8652-517P X8652-640P
4		1. Black 2. Green 3. Red 4. White	600V, 20A	12	6' 12' 18'	X8653-516P X8653-517P X8653-640P

Note: Special lengths available upon request — consult factory.

SPECIFICATIONS CHANGE-OUT PLUGS

Series A

- 2-9 Pole Configurations
- 2-4 Pole; #14 AWG, 12 AWG, 10 AWG
- 5-9 Pole; #18 AWG
- Nylon or Zinc Diecast Hardware

Series B

- 2-8 Pole Configurations
- 2-7 Pole; #10 AWG
- 8 Pole; #14 AWG
- Anodized Aluminum Hardware



TECHNICAL DATA

Agency Approvals

UL Recognition:

CSA Recognition:

File #E169897

File #LR13963

Electrical Data

Current Rating:

Voltage Rating:

Dielectric Withstand Voltage:

See chart with part number detail

See chart with part number detail

2200 VAC

Environmental Data

Protection:

Temperature Range:

NEMA 1, 3, 4, 6P and 13; IEC IP 68

(Nylon: NEMA 4X, Hose down pressure 1000 PSI)

-20°C to +105°C

Material Data

Body:

Cable:

Contacts:

Coupling Nut:

Black flame resistant PVC, Neoprene

STOOW, SO

Series A Machined Brass; Series B copper

Series A Zamak, nylon 6/6 weather stabilized

Series B Machined Aluminum

DIMENSIONS

