

Product Number: 64836

Order Abbreviation: M70/U/MED

General Description: 70W METALARC PULSE START quartz metal halide lamp, reduced color shift, MED base, E17 bulb, enclosed fixture rated, universal burn, clear, 4400K



Product Information

Abbrev. With Packaging Info.	M70UMED 20/CS 1/SKU
ANSI Code	M98/E
ANSI Code 2	M98/E
Approx. Lumens (initial - horizontal)	6000
Approx. Lumens (initial - vertical)	5600
Approx. Lumens (mean - vertical)	3300
Arc Length (in)	0.37
Arc Length (mm)	9.5
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Average Rated Life - Vertical (hr)	12000
Avg Rated Life (hrs)	12000
Base	E26 Medium
Bulb	ED17
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	2.098
Diameter (mm)	53.30
Family Brand Name	Metalarc® Pulse Start
Fixture Requirement	E
Hot Restrike Time (min)	5-7
Lamp Finish	Clear
Light Center Length - LCL (in)	3.4
Light Center Length - LCL (mm)	86
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752

22/10/2020

Product Details

Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.4
Maximum Overall Length - MOL (mm)	138
Nominal Voltage (V)	85.00
Nominal Wattage (W)	70.00
Operating Position	HID_POSITION32.GIF
Warm-up Time (min)	2-4