

Product Datasheet

Characteristic

9007C62D

LIMIT SWITCH 600V 10AMP C +OPTIONS



Main

range of product	9007
series name	Heavy duty
product or component type	Limit switch
product specific application	Standard box
device short name	9007C
body type	Plug-in
head type	Plunger head
material	Metal
fixing mode	By the body
movement of operating head	Linear
type of operator	Steel spring return roller plunger (-)
switch actuation	By 30° cam
type of approach	2 directions lateral approach
electrical connection	(AWG 22...AWG 12) screw-clamp terminals, 1...2
cable entry	1 entry for 1/2" - 14 NPT conforming to ANSI B1.20.1
number of poles	2
contacts type and composition	2(NC-NO)
contact operation	Snap action
positive opening	Without
sale per indivisible quantity	1

Complementary

body material	Zinc
head material	Zinc
function available	-
switch function	DPDT-DB
contact form	Form ZZ
contacts material	Silver contacts
terminals description ISO n°1	(5-6)NC (7-8)NO (1-2)NC

	(3-4)NO
repeat accuracy	+/- 0.001 in linear travel of cam
[Ie] rated operational current	1.2 Aat 600 V AC, A600 conforming to NEMA 1.5 Aat 480 V AC, A600 conforming to NEMA 3 Aat 240 V AC, A600 conforming to NEMA 6 Aat 120 V AC, A600 conforming to NEMA 0.11 Aat 250 V DC, R300 conforming to NEMA 0.55 Aat 125 V DC, R300 conforming to NEMA
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	600 V degree of pollution 3 conforming to UL 508for contact block 600 V degree of pollution 3 conforming to CSA C22.2 No 14for contact block
[Uimp] rated impulse withstand voltage	2.5 kV ACfor 1 min conforming to CE 2.2 kV ACfor 1 min conforming to UL 2.64 kV ACfor 1 s conforming to CSA
short-circuit protection	10 A by CC fuse, protection type: non-time delay
electrical durability	1000000 cycles
local signalling	Without
mechanical durability	10000000 cycles
width	1.55 in
height	4.98 in
depth	1.79 in
product weight	1.25 lb(US)

Environment

shock resistance	60 gn (duration = 9 ms) conforming to IEC 60068-2-27
vibration resistance	25 gn (f = 10...150 Hz) conforming to IEC 60068-2-6
NEMA degree of protection	NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 6 conforming to Nema type 250 NEMA 6P conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250 NEMA 1 conforming to Nema type 250
IP degree of protection	IP67 conforming to IEC 60529
electrical shock protection class	Class 0 conforming to IEC 61140
ambient air temperature for operation	-20...185 °Ffor standard environment
ambient air temperature for storage	-20...185 °F
environmental characteristic	Standard environment
protective treatment	Epoxy powder coat

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1150 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations