## Product data sheet Characteristics

# NSYCVF300M230PF

ClimaSys forced vent. IP54, 300m3/h, 230V, with outlet grille and filter G2





#### Overview

Lead time	Usually Ships within 4 Weeks	
-----------	------------------------------	--

#### Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 79253.03 Gal/hr(US) (300 m3/h) at 50 Hz Free flow rate with standard filter: 92461.87 Gal/hr(US) (350 m3/h) at 60 Hz
[Us] rated supply voltage	145253 V
Input voltage	230 V 50/60 Hz

#### Complementary

o impromormary	
Absorbed power	36 W 50 Hz 37 W 60 Hz
Line Rated Current	0.16 A 60 Hz
	0.17 A 50 Hz
Noise level < at	5556 dB
Bearing type	Ball
Height	External 10.55 in (268 mm)
Width	External 9.76 in (248 mm)
Depth	External 4.57 in (116 mm)
Cut-out dimensions	223 x 223 mm
Net Weight	2.87 lb(US) (1.3 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
Color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	14158 °F (-1070 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Maximum pressure	158 Pa flow rate 0 m³/h
Connections - Terminals	Faston connector
IP degree of protection	IP54

1 axial motor	
, ,	
1 filter front of axial motor	
1 outlet grille front	
1 cut-out template	
1 power cord	
Surrounding environment must be relatively clean	
Filter must be cleaned and replaced regularly	
Outside temperature must be 5 °C lower than inside temperature	
Overfrequent filter replacement should be avoided	
Flow rates depends on the work point, see ProClima software	
	1 cut-out template 1 power cord  Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided

## Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151286
Returnability	No
Country of origin	FR

### **Packing Units**

i doning office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.28 in (18.5 cm)
Package 1 Width	10.04 in (25.5 cm)
Package 1 Length	10.63 in (27.0 cm)
Package 1 Weight	3.62 lb(US) (1.642 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	11.02 in (28.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	16.48 lb(US) (7.476 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	64
Package 3 Height	37.40 in (95.0 cm)
Package 3 Width	31.50 in (80.0 cm)
Package 3 Length	47.24 in (120.0 cm)
Package 3 Weight	297.62 lb(US) (135.0 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☐ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€ Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	

### Contractual warranty

Warranty	18 months