

97599 - F18DBX/830/ECO4P

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse









CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-In

Bulb T4
Base G24q-2
Equivalent Wattage (NOM) 65.0 W

Rated Life (NOM) 17000.0/20000.0 h

Starting Temperature (MIN) 0.0 °C
Cathode Resistance (NOM) 6.05 Ohm
Mercury Content (NOM) 3.0 mg
Picograms of Mercury (NOM) 181.9 pg

Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant Facilities:Retail

Primary Application Facilities; Retail
Display; Hospitality; Office; Restaurant; W.

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 1250.0 Mean Lumens (NOM) 970.0 Nominal Initial Lumens per Watt 69.44444

(NOM)

Color Temperature (NOM) 3000.0 K Color Rendering Index (CRI) 82.0

(NOM)

ELECTRICAL CHARACTERISTICS

Wattage (NOM) 18.0
Voltage (NOM) 100.0
Current (max) (NOM) 5.25 A
Open Circuit Voltage (after preheating) (MAX)
Open Circuit Voltage Across 198.0 V

Starter (MIN)

Lamp Current (NOM)

Preheat Voltage (MIN)

Current Crest Factor (MAX)

Supply Current Frequency

0.22 A

4.25 V

1.7

60.0 Hz

(NOM)

DIMENSIONS

Maximum Overall Length (MOL) (NOM)

Nominal Length (NOM)

Base Face to Top of Lamp (NOM)

5.800 in(147.3 mm)

5.800 in(147.3 mm)

5.800 in(147.3 mm)

5.200 in(132.1 mm)

PRODUCT INFORMATION

Product Code 97599

Description F18DBX/830/ECO4P ANSI Code 60501-IEC-2518-2 Standard Package BUNDLE

50

Standard Package GTIN

Standard Package Quantity

Sales Unit Unit
No Of Items Per Sales Unit 1
No Of Items Per Standard 50

Package

UPC 043168975995

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Based on 60Hz reference circuit.
- Cold cathode resistance is approximately 6.0 Ohms.
- Fluorescent lamp lumens decline during life