

CH364

200A 3P Type1 600VAC/DC Heavy Duty Fusible Safety Switch



Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	200 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Wire Size	AWG 6...250 kcmil copper or aluminium
Maximum Horse Power Rating	50 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 125 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 60 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 150 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 40 Hp 250 V DC 50 hp at 600 V DC
Height	29 in (736.60 mm)
Maximum Width	18.5 in (469.90 mm)
Depth	8.25 in (209.55 mm)
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in ² (13.30...127 mm ²) AWG 6...250 kcmil)

Environment

Certifications	CSA
Enclosure Rating	NEMA 1 galvanized steel

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	00785901995395
Nbr. of units in pkg.	1
Package weight(Lbs)	45.02 lb(US) (20.42 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	8.50 in (21.590 cm)
Package 1 width	19.50 in (49.530 cm)
Package 1 Length	30.50 in (77.470 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes