

Low Profile Fiber Optic Wall Mount Patch Panel - 4 Adapter Strips

Description	Wirewerks low profile fiber optic wall mount patch panel is designed for fiber interconnects and splicing while offering a discreet profile. The patch panel is made of 16 gauge cold rolled steel (CRS) with a black powder coated finish, and accepts four adapter strips. Adapter strips, or cassettes up to 96 fibers can be installed into the 4 LGX cut-outs using their push pin mechanism. Four self-sealing grommets accommodate multiple cable entrance and exits. This low profile patch panel features two separate doors which are lockable with key locks (not included, part number WW000014) to control access to the distribution or patch sides, providing additional network security.	
Features and Benefits	<p>Low profile design for space saving</p> <p>Fits 4 LGX adapter strips, and cassettes</p> <p>Fits 4 slim splice trays part number SPL-MSPL6 (not included). For technical reference, refer to PDS-0126</p> <p>Integrated splice tray holder</p>	<p>4 grommets to limit contaminant intrusion at the cable entrance points</p> <p>Maximum capacity of 96 fiber</p> <p>Both doors are Lockable to protect your network (key lock not included)</p> <p>Installation hardware and instructions manual included</p>
Applications	<p>Data center</p> <p>Telecommunications room</p>	<p>Equipment room</p> <p>Consolidation point</p>
Certification and Compliance	<p>TIA-569-B</p> <p>CEA/EIA-310-E</p> <p>ANSI/TIA/EIA-606-A</p> <p>UL 94</p> <p>RoHS</p>	<p>Commercial Building Standard for Telecommunications Pathways and Spaces. Cabinets, Racks, Panels and Associated Equipment standard.</p> <p>Administration Standard for Telecommunications Infrastructure.</p> <p>Tests for Flammability of Plastic Material for Parts in Devices and Appliances.</p> <p>Directive on Restriction of Hazardous Substances.</p>



Low Profile Fiber Optic Wall Mount Patch Panel - 4 Adapter Strips

wirewerks



Ordering Information

Description	Part Number
Low profile fiber optic wall mount patch panel 4 adapter strips	PP-WM4SD

Packaging

Description
Cardboard box, 1 unit per box.

Inclusion

Description
1 instructions manual, 4 wood screws 10 x 0.75 inch, 2 nylon tie wraps, 4 Velcro tie wraps 11.8 inches long, 1 self-adhesive port ID label, 1 warning label.

Physical Characteristics

Parameter	Value
Fiber count capacity	96 fibers maximum
Plastic materials	UL 94V-0 thermoplastic
Panel material	16 Gauge cold rolled steel (CRS)
Panel finish	Black Sandex
Overall dimensions	381.6 mm (15.625 in) x 381 mm (15 in) x 88.9 mm (3.5 in)

Mechanical Characteristics

Parameter	Value
Installation temperature	-25° C (-13° F) ~ 40° C (104° F)
Storage temperature	-25° C (-13° F) ~ 55° C (131° F)
Relative humidity	≤ 85% (30° C)